

Add-on LED for curb alert CA5/CA6/CA7/CA12/CA13/CA14 (Kit # 5000-CLED)

Please read thoroughly before starting installation and check that kit contents are complete.

Items Included in the Kit:

LED with 6ft cable
1/8" Y-splitter

Tools & Supplies Needed:

Drill
Drill Bits/
Zip ties
Plastic panel removal tools

Safety Precautions:

- Work in well ventilated area that is clear of obstructions.
- Secure vehicle with tire chucks in both front and rear of tires.
- Turn vehicle accessories OFF and ensure ignition key is in OFF position.
- Wear safety goggles and snug fitting clothes.
- Use tools only for their intended purpose and which are in good repair.
- Only perform this task if confidence, skill, and physical ability permit.

NOTE: We strive to provide accurate and up-to-date installation instructions. For the latest full color instructions, as well as an installation video, please visit www.brandmotion.com



1. Find a visible location for the LED.
2. If you want to flush mount the LED in the plastic, (make sure to have at least 2" behind the plastic for the LED to fit into) drill a 5/16" hole to put the led through.
3. Some of the heat shrink will need to be cut back on the LED to take the red cover off.



4. To remove the red cover, hold the black part of the LED and twist and pull off the red cover.



5. Once installed in the dash, run the cable over to the curb alert control module.
6. Unplug the speaker 1/8" plug from the control module and plug in the single male end of the Y-splitter to the speaker output port.

INSTALLATION INSTRUCTIONS

7. Then plug the speaker and the LED into the 2 open ends of the Y-splitter cable.
8. The LED will flash each time the speaker chirps.

