

## 9002-9701 Installation Instructions (Infinity Manual Dimming Wedge Mount Mirror)

### IMPORTANT:

Read instructions before installing. For the latest full color instructions please visit [www.brandmotion.com](http://www.brandmotion.com)

NOTE 1: This mirror has a Wedge/ D-tab style mounting base. Please check our application guide to ensure it is compatible with your vehicle (for specific applications, adapters are available separately). In some cases, it may be necessary to remove a cover to access the wedge mount on the windshield and/or modify the cover slightly to clear the mirror mount.

NOTE 2: If your vehicle is equipped with a mirror cover, mirror adjustability may be restricted.

To install:

1. Loosen vehicle mirror screw using a T20 Torx driver and remove existing vehicle mirror.  
**CAUTION:** Do not twist mirror as windshield damage could result.
2. Carefully slide supplied Mirror onto the windshield tab.
3. Torque supplied Mirror screw to 1.8 Nm (16 lb-in) and do not exceed 2.2 Nm (19.5 lb-in).



To operate, push tab on bottom of mirror forward to dim. Pull tab backward to undim mirror.

## 9002-9701 Installation Instructions (Infinity Manual Dimming Wedge Mount Mirror)

### IMPORTANT:

Read instructions before installing. For the latest full color instructions please visit [www.brandmotion.com](http://www.brandmotion.com)

NOTE 1: This mirror has a Wedge/ D-tab style mounting base. Please check our application guide to ensure it is compatible with your vehicle (for specific applications, adapters are available separately). In some cases, it may be necessary to remove a cover to access the wedge mount on the windshield and/or modify the cover slightly to clear the mirror mount.

NOTE 2: If your vehicle is equipped with a mirror cover, mirror adjustability may be restricted.

To install:

1. Loosen vehicle mirror screw using a T20 Torx driver and remove existing vehicle mirror.  
**CAUTION:** Do not twist mirror as windshield damage could result.
2. Carefully slide supplied Mirror onto the windshield tab.
3. Torque supplied Mirror screw to 1.8 Nm (16 lb-in) and do not exceed 2.2 Nm (19.5 lb-in).



To operate, push tab on bottom of mirror forward to dim. Pull tab backward to undim mirror.