

ADAS add-on display (Kit # ADAS-1030)

Please read thoroughly before starting installation and check that kit contents are complete.

Items Included in the Kit:

Dash mounted display
These instructions

Tools & Supplies Needed:

Wire strippers
Wire cutters
Electrical tape
Zip ties
Plastic panel removal tools
Digital Volt Meter / BCM safe test light
Screwdriver
Socket set
Wrench

Safety Precautions:

- Work in well ventilated area that is clear of obstructions.
- Secure vehicle with tire chucks in both front and rear of tires.
- Turn vehicle accessories OFF and ensure ignition key is in OFF position.
- Wear safety goggles and snug fitting clothes.
- Use tools only for their intended purpose and which are in good repair.
- Only perform this task if confidence, skill, and physical ability permit.

NOTE: We strive to provide accurate and up-to-date installation instructions. For the latest full color instructions, as well as an installation video, please visit www.brandmotion.com



1. Plug the white plug on the display into the HUB that is included with the main ADAS-1000 unit.
2. Connect the RED wire to 12 accessory.
3. Connect the BLACK wire to ground.
4. Find a good location in the vehicle to mount the display. To the left side of the dash or center is a good visible location to mount it.
5. Clean mounting location with alcohol to remove any dirt or grease.