

**5" Digital Display Monitor
(Kit # FLTW-7650)**

Please read thoroughly before starting installation and check that kit contents are complete.

Items Included in the Kit:

5" Display monitor with removable sunshade
Power and Input cable
Video Input Harness
Mounting Bracket
Thumb Screws
Allen Wrench
Aux A/V harness (for front input)
Remote
These Instructions

Tools & Supplies Needed:

Electrical tape
Zip ties
Plastic panel removal tools
Digital Volt Meter / BCM safe test light



Safety Precautions:

- Work in well ventilated area that is clear of obstructions.
- Secure vehicle with tire chucks in both front and rear of tires.
- Turn vehicle accessories OFF and ensure ignition key is in OFF position.
- Wear safety goggles and snug fitting clothes.
- Use tools only for their intended purpose and which are in good repair.
- Only perform this task if confidence, skill, and physical ability permit.

NOTE: We strive to provide accurate and up-to-date installation instructions. For the latest full color instructions, as well as an installation video, please visit www.brandmotion.com

1. RED wire connects to accessory power.
2. BLACK wire connects to ground.
3. Connect the appropriate trigger wire to reverse for the input you intend to use. The BROWN wire is for the CH1 input, the BLUE wire is for the CH2 input, and the GRAY wire is for the CH3 input.
4. Connect the power harness to the monitor.
5. Connect the video input harness to the input you selected when you connected the reverse trigger wire in step 3. (The BROWN wire is for the CH1 input, the BLUE wire is for the CH2 input, and the GRAY wire is for the CH3 input.)
6. The Allen wrench is used for screw that allow you to "lock" the mounting bracket in position.
7. If using our 9002-7607, 9002-7608, 9002-7609, FLTW-7604, or FLTW-7620, they will directly plug into the CH1, CH2, or CH3 for video and power.