

INSTALLATION INSTRUCTIONS

7" Digital Display Monitor (Kit # FLTW-7670)

Please read thoroughly before starting installation and check that kit contents are complete.

Items Included in the Kit:

7" Display Monitor with Removable Sunshade Power and Input Box w/Cable Video Input Harness Mounting Stand Remote Allen Wrench These instructions

Tools & Supplies Needed:

Electrical tape
Zip ties
Plastic panel removal tools
Digital Volt Meter / BCM safe test light



Safety Precautions:

- Work in well ventilated area that is clear of obstructions.
- Secure vehicle with tire chucks in both front and rear of tires.
- Turn vehicle accessories OFF and ensure ignition key is in OFF position.
- Wear safety goggles and snug fitting clothes.
- Use tools only for their intended purpose and which are in good repair.
- Only perform this task if confidence, skill, and physical ability permit.



INSTALLATION INSTRUCTIONS

- 1. RED wire connects to accessory power.
- 2. BLACK wire connects to ground.
- 3. GREEN wire connects to the vehicle's 12-volt reverse wire.
- 4. Connect the power harness to the monitor.
- Connect the video input harness to the power harness. If using the display for a back-up camera, connect to CAM2. It will trigger off reverse.
- 6. CAM1 can be used for "always on" video input.
- 7. The Allen wrench is used for screws that allow you to "lock" the mounting bracket in position.
- 8. If using our 9002-7607, 9002-7608, 9002-7609, FLTW-7604, or FLTW-7620 they will directly plug in to the C1 or C2 for video and power.